

C E R W I N - V E G A

	D-1	D-2	D-3	D-5	D-7	D-9
DESCRIPTION	8" 2-WAY	10" 2-WAY	10" 3-WAY	12" 3-WAY	12" 3-WAY	15" 3-WAY
FREQUENCY RESPONSE	30Hz-20kHz	30Hz-20kHz	30Hz-20kHz	32Hz-20kHz	25Hz-20kHz	29Hz-20kHz
POWER HANDLING CAPACITY, MINIMUM/MAXIMUM	5/100 WATTS	5/125 WATTS	5/125 WATTS	5/150 WATTS	5/200 WATTS	5/350 WATTS
SENSITIVITY, 1W AT 1M	92dB	94dB	94dB	96dB	98dB	101dB
NOMINAL IMPEDANCE	8 OHMS	8 OHMS	8 OHMS	8 OHMS	8 OHMS	8 OHMS
DISTORTION, MIDBAND AT 96dB/M, THD & IM	0.8%	0.7%	0.7%	0.6%	0.5%	0.5%
MAXIMUM OUTPUT LEVEL PAIR AT 3M, FULL POWER	111dB	114dB	114dB	117dB	120dB	125dB
LF DRIVER VC SIZE	1.5"	1.5"	1.5"	2"	2"	2"
LOW FREQUENCY DRIVER	8" CAST ALUMINUM FRAME	10" CAST ALUMINUM FRAME	10" CAST ALUMINUM FRAME	12" CAST ALUMINUM FRAME	12" CAST ALUMINUM FRAME	15" CAST ALUMINUM FRAME
MID FREQUENCY DRIVER	—	—	6" CONE	6" CONE	(2) 6" CONES	(2) 6" CONES
HIGH FREQUENCY DRIVER	1" VOICE COIL HORN	1" VOICE COIL HORN	1" VOICE COIL HORN	1" VOICE COIL HORN	1" VOICE COIL HORN	1" VOICE COIL HORN
CROSSOVER FREQUENCIES	3000Hz	3000Hz	700Hz/3500Hz	700Hz/3500Hz	500Hz/3500Hz	500Hz/3500Hz
CONNECTIONS	LOW RESISTANCE PUSH TERMINALS	LOW RESISTANCE PUSH TERMINALS	LOW RESISTANCE PUSH TERMINALS	LOW RESISTANCE PUSH TERMINALS	LOW RESISTANCE PUSH TERMINALS	LOW RESISTANCE PUSH TERMINALS
PROTECTION	SELF-RESETTING CIRCUIT BREAKER FOR TWEETER	SELF-RESETTING CIRCUIT BREAKER FOR TWEETER	SELF-RESETTING CIRCUIT BREAKER FOR TWEETER	SELF-RESETTING CIRCUIT BREAKER FOR TWEETER	SELF-RESETTING CIRCUIT BREAKER FOR TWEETER, OVERALL FUSE	SELF-RESETTING CIRCUIT BREAKER FOR TWEETER, OVERALL FUSE
LEVEL CONTROLS	—	—	TWEETER	TWEETER	TWEETER, MIDRANGE	TWEETER, MIDRANGE
ENCLOSURE TYPE	VENTED, DIRECT RADIATING	VENTED, DIRECT RADIATING	VENTED, DIRECT RADIATING	VENTED, DIRECT RADIATING	VENTED, DIRECT RADIATING	VENTED, DIRECT RADIATING
ENCLOSURE CONSTRUCTION	3/4" PARTICLE BOARD, BRACED	3/4" PARTICLE BOARD, BRACED	3/4" PARTICLE BOARD, BRACED	3/4" PARTICLE BOARD, BRACED	3/4" PARTICLE BOARD, BRACED	3/4" PARTICLE BOARD, BRACED
FINISH	SCUFF-RESISTANT WOODGRAIN VINYL	SCUFF-RESISTANT WOODGRAIN VINYL	SCUFF-RESISTANT WOODGRAIN VINYL	SCUFF-RESISTANT WOODGRAIN VINYL	SCUFF-RESISTANT WOODGRAIN VINYL	SCUFF-RESISTANT WOODGRAIN VINYL
DIMENSIONS H X W X D	20" X 11" X 10"	23.5" X 14" X 10"	26.5" X 14" X 10.69"	27.63" X 16.25" X 10.69"	34" X 16" X 14.75"	35.5" X 18" X 17.75"
GROSS WEIGHT	(2) 49 lbs.	34.5 lbs.	39 lbs.	41 lbs.	70 lbs.	85 lbs.