

AMT SPECIFICATIONS

AMT SERIES	AMT MONITOR	AMT ID
Power Capacity	400 Watts	400 Watts
Frequency Response	30-23+3db	35-23+3dB
Crossover Frequency	800 Hz	800 Hz
Efficiency: SPL @ 1w/1m	93dB	91dB
Midrange Control	800Hz to 5KHz(+3dB to-6dB)	800Hz to 5KHz(+3dB to-6dB)
Brilliance Control	5KHz to 23 kHz (+5dB)	5KHz to 23 kHz (+5dB)
Low frequency	12" Polypropylene	12" Polypropylene
Bass Radiator	12" EPS Styrene Foam / laminated	12" EPS Styrene Foam / laminated
Heil Air-Motion	Total Radiating Area 21 1/2 sq.in.	Total Radiating Area 21 1/2 sq.in.
	Transformation Ratio 5.3:1	Transformation Ratio 5.3:1
	Magnet Assembly Weight 12lbs 5oz	Magnet Assembly Weight 12lbs 5oz
Cabinet Dimensions	39 1/4" x 15 3/4" x 15 3/4"	36 1/2" x 16 1/4 x 16 1/4
Shipping Weight	110lbs	88lbs
Impedance	6 ohms	6 ohms
Dispersion	1200 Horizontal 300 Vertical	1200 Horizontal 300 Vertical
	Magnet Assembly Weight 7lbs 5 oz	Magnet Assembly Weight 7lbs 5 oz
Finish	Black Walnut Veneer	Black Walnut or Oiled Walnut Veneer

